MultiTouch Table

55“ 4K & 65“ 4K

AVR EDGE

Mod. 1

Mod 2

The **AVR EDGE 4K** MultiTouch Table is an interactive table solution to be used at events, museums, trade shows or in retail stores. Besides the exceptional design, the table operates with the state-of-the-art InGlass Touch sensor. Also, it‘s possible to store a powerful PC Workstation inside of the table body.

NextGad- Thomashofstraße 27/29, 76228 Karlsruhe, Germany Phone: +49 (0) 721 46 47 12 41 - Web: wwwnextgad.eu - Email: info@nextgad.eu

55“

AVR EDGE 55“ 4K - AVRE55T

Diagonal	1397 m (55“)
Resolution	3840x2160 px @ 60 Hz
Panel	AMVA3
Viewing Area	1209.6 x 680.4 mm
Brightness	450 cd/m2
Aspect Ratio	16:9
Contrast	4000:1
Viewing Angle	178° H/V
Colors	16,7 Mil.
Response Time	8 ms
Touch Technology	InGlass™ Touch Technology
Touch Points	40 Independent Touch Points
Touch Accuracy	<2 mm
Touch Response Time	<15 ms
Touch Reporting Rate	100 Hz
Touch Resolution	19354 x 10886
Touch Method	Fingers, gloves, soft tip styluses and soft objects are detected – min. size 4 mm
Connections	HDMI / DisplayPort
Controls	Keypad
Dimensions (mm)	1300 x 770 x 84 mm
Weight	40 Kg.
Operating Conditions	+0 to +40 °C
Continuous Operation	24/7
Power Consumption	300W (max)
Surface / Glass	Edge-to-edge flush design – no bezel Chemically strengthened safety glass 3.2 mm
Operating Systems	Windows 8 / Windows 10 / Linux / Android
Warranty	2 years parts and labor
Delivered Contents	Power Cord (EU)

65“

AVR EDGE 65“ 4K - AVRE65T

Diagonal	1652 m (65“)
Resolution	3840x2160 px @ 60 Hz
Panel	AMVA3
Viewing Area	1428.5 x 803.5 mm
Brightness	450 cd/m2
Aspect Ratio	16:9
Contrast	5000:1
Viewing Angle	178° H/V
Colors	16,7 Mil.
Response Time	6.5 ms
Touch Technology	InGlass™ Touch Technology
Touch Points	40 Independent Touch Points
Touch Accuracy	<2 mm
Touch Response Time	<15 ms
Touch Reporting Rate	100 Hz
Touch Resolution	19354 x 10886
Touch Method	Fingers, gloves, soft tip styluses and soft objects are detected – min. size 4 mm
Connections	HDMI / DisplayPort
Controls	Keypad
Dimensions (mm)	1518.5 x 893.5 x 74.9 mm
Weight	56 Kg.
Operating Conditions	+0 to +40 °C
Continuous Operation	24/7
Power Consumption	350W (max)
Surface / Glass	Edge-to-edge flush design – no bezel Chemically strengthened safety glass 3.2 mm
Operating Systems	Windows 8 / Windows 10 / Linux / Android
Warranty	2 years parts and labor
Delivered Contents	Power Cord (EU)